



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX PTB 06.0085** Issue No.: **0**

Status: **Current**

Date of Issue: **2006-09-19** Page 1 of **3**

Applicant: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg (Württ.)
Germany

Electrical Apparatus: **Control box, type 8125/5000-2-C1309 and 8125/5917-2-C1310**
Optional accessory:

Type of Protection: **Type of protection "n", Increased Safety, Intrinsic Safety, Protection by enclosures**

Marking: **Ex nAC e ib [ia/ib] IIC T4**
Ex tD A22 IP65 T 70 °C

*Approved for issue on behalf of the IECEx
Certification Body:*

Dr.-Ing. Uwe Klausmeyer

Position:

Head of section "Flameproof Enclosures"

*Signature:
(for printed version)*

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](http://www.iecex.com).

Certificate issued by:

**Physikalisch-Technische
Bundesanstalt (PTB)**

Bundesallee 100
38116 Braunschweig
Germany





IECEX Certificate of Conformity

Certificate No.: **IECEX PTB 06.0085**

Date of Issue: **2006-09-19**

Issue No.: **0**

Page **2** of **3**

Manufacturer: **R. STAHL Schaltgeräte GmbH**
Am Bahnhof 30
74638 Waldenburg (Württ.)
Germany

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2004 Edition: 4.0	Electrical apparatus for explosive gas atmospheres - Part 0: General requirements
IEC 60079-11 : 1999 Edition: 4	Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'
IEC 60079-15 : 2001 Edition: 2	Electrical apparatus for explosive gas atmospheres - Part 15: Type of protection 'n'
IEC 60079-7 : 2001 Edition: 3	Electrical apparatus for explosive gas atmospheres - Part 7: Increased safety 'e'
IEC 61241-0 : 2004 Edition: 1	Electrical apparatus for use in the presence of combustible dust - Part 0: General requirements
IEC 61241-1 : 2004 Edition: 1	Electrical apparatus for use in the presence of combustible dust - Part 1: Protection by enclosures "tD"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[DE/PTB/ExTR06.0077/00](#)

Quality Assessment Report:

[DE/PTB/QAR06.0001/00](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX PTB 06.0085**

Date of Issue: **2006-09-19**

Issue No.: **0**

Page **3** of **3**

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

Description of equipment

The control box, type 8125/5000-2-C1310 consists of an enclosure out of sheet-steel or stainless sheet-steel designed to type of protection Increased Safety "e" and Protection by enclosures "tD". The enclosure is equipped with a Remote I/O System (IECEX PTB 06.0001X), terminals and cable glands.

The control box, type 8125/5917-2-C1309 is additionally equipped with magnets in the type of protection Intrinsic Safety "ia".

The control box is intended for permanent installation. It is designed to record and output process control signals between hazardous location transducers and sensors and a non-hazardous location automation system.

All components are separately certified. The composition of the protection symbol will be based on the types of protection of the components actually used.

Technical data

Rated voltage	up to	240 V
Rated cross section	max.	16 mm ²
Ambient temperature range	-20 °C to +50 °C	
Protection against contact, entry of solids and water according to IEC 60529	≥ IP65	

Notes for installation and use

Equipment of the type of protection Intrinsic Safety "i" shall be installed in such a way that the clearances and creepage distances between intrinsically safe and non-intrinsically safe circuits as set forth in IEC 60079-14 are duly accounted for.

If the clearance requirements for the connectors as specified in IEC 60079-11 cannot be safeguarded with the system installation and layout, wiring, that meets the quality criteria Increased Safety "e" shall be used, or the wiring shall be of the fail-safe type.

When using more than one intrinsically safe circuit, the rules and regulations for interconnection shall duly be observed.

CONDITIONS OF CERTIFICATION: NO