

Control Equipment

Time Relay for Panel Mounting

Series 8214



10026E00

Time Relay for Panel Mounting

Series 8214

Both pre-selected time range and time setting can be adjusted externally during operation. The timer relays can be supplied in pick-up delayed and drop-out delayed versions.

Selection Table

Version	Description		Ordering code	Weight kg	
8214 Time relay	Analogue	on-delayed	0,1 s ... 30 h	8214/122-2-S03	4,700
			0,2 s ... 60 h		
	Multifunction unit		0,05 s ... 100 h	8214/122-2-S03	4,700

Add. to ordering code

Time range
Voltage and frequency
possible 24 V, 42 V, 115 V, 230 V, 50 or 60 Hz

Technical Data

Explosion protection	⊕ II 2 G EEx de IIC T6
Certificates	PTB 02 ATEX 1102
Other Certificates	IECEX
Enclosure material	Aluminium, powder coated
Time relay	
Rated voltage	24 V, 42 V, 115 V, 230 V, 50 or 60 Hz
Contacts	
on-delayed	1 immediate and 1 delayed changeover
Operating temperature range	- 10 °C ... + 40 °C
Mechanical data	
Degree of protection	IP 54

We reserve the right to make alterations to the technical data, weights, dimensions, designs and products available without notice. The illustrations cannot be considered binding.