


**Trumpet Threaded Cable Nut Made of Moulded Plastic**  
**Series HSK-K-MZ-Ex**

- Version Ex e II
- Degree of protection IP 68
- For use in
  - Zone 1 and Zone 2
  - Zone 21 and Zone 22
- Usable for portable equipment



09904E00



**Selection table**

Thread	Cable dia. range [mm]	Dimensions [mm]			Ordering code	Weight kg
		H	SW	GL		
AG						
M 16 x 1.5	4 ... 8	29	19	15	<b>3516750</b>	0,012
M 20 x 1.5	6 ... 12	35.5	24	15	<b>3516760</b>	0,022
M 25 x 1.5	13 ... 18	41	33	11	<b>3516770</b>	0,035
M 32 x 1.5	18 ... 25	49	42	11	<b>3516780</b>	0,065
M 40 x 1.5	22 ... 32	58	53	13	<b>3516790</b>	0,104
M 50 x 1.5	32 ... 38	61.5	60	13	<b>3516800</b>	0,174
M 63 x 1.5	37 ... 44	62	65 / 68	14	<b>3516810</b>	0,270

**Technical Data**

Explosion protection	Ⓢ II 2G Ex e II Ⓢ II 1D Ex tDA20 IP68
Certificates	KEMA 99 ATEX 6971 X
Other certificates	IECEX, GL
Material	
Cable gland	Polyamide / Aluminium
Gaskets	NBR
Degree of protection	IP 68 - 10 bar (in specified terminal area)
Ambient conditions	- 20 °C ... + 70 °C

We reserve the right to make alterations to the technical data, weights, dimensions, designs and products available without notice. The illustrations cannot be considered binding.

