

## Installation Material and Accessories

### Trumpet Threaded Cable Nut Made of Metal

#### Series HSK-MZ-Ex




09908E00

#### Trumpet Threaded Cable Nut Made of Metal

##### Series HSK-MZ-Ex

- Version EEx e II
- IP 68
- For use in
  - Zone 1 and Zone 2
  - Zone 21 and Zone 22
- Usable for portable equipment



09906E00

#### Selection table

Thread	Cable dia. range [mm]	Dimensions [mm]			Ordering code	Weight kg
		H	SW	GL		
AG						
M 16 x 1.5	4 ... 8	29	19	6	3516830	0,028
	6 ... 10	30	20	6	3516840	0,028
M 20 x 1.5	6 ... 12	33	22	6	3516850	0,051
	10 ... 14	33	24	6	3516860	0,051
M 25 x 1.5	14 ... 18	37	30	7	3516870	0,082
M 32 x 1.5	20 ... 25	43	40	8	3516880	0,152
M 40 x 1.5	24 ... 32	50	50	8	3516890	0,242
M 50 x 1.5	32 ... 38	51	57	9	3516900	0,560
M 63 x 1.5	37 ... 44	52	64/68	10	3516910	0,616

#### Technical Data

Explosion protection	II 2 GD EEx e II
Certificates	KEMA 99 ATEX 6971 X
Material	
Cable gland	Brass nickel-plated
Formed seal	NBR
O-ring	NBR
Terminal protection	Polyamide
Degree of protection	IP 68 - 10 bar (in specified terminal area)
Ambient temperature	- 60 °C ... + 105 °C

We reserve the right to make alterations to the technical data, weights, dimensions, designs and products available without notice. The illustrations cannot be considered binding.